



PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification ⁷ : A61B 18/14</p>	<p>A1</p>	<p>(11) International Publication Number: WO 00/44295 (43) International Publication Date: 3 August 2000 (03.08.00)</p>
<p>(21) International Application Number: PCT/US00/02155 (22) International Filing Date: 25 January 2000 (25.01.00) (30) Priority Data: 09/238,965 27 January 1999 (27.01.99) US (71) Applicant: SENORX, INC. [US/US]; Suite 144, 13766 Alton Parkway, Irvine, CA 92618 (US). (72) Inventors: BURBANK, Fred, H.; 30982 Steeplechase Drive, San Juan Capistrano, CA 92675 (US). LUBOCK, Paul; 30 Bethany, Laguna, CA 92677 (US). (74) Agents: CHOW, Y., Ping et al.; Heller Ehrman White & McAuliffe, 525 Univeristy Avenue, Palo Alto, CA 94301-1900 (US).</p>		<p>(81) Designated States: AE, AL, AM, AT, AT (Utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), DM, EE, EE (Utility model), ES, FI, FI (Utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KR (Utility model), KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).</p> <p>Published <i>With international search report.</i></p>
<p>(54) Title: TISSUE SPECIMEN ISOLATING AND DAMAGING DEVICE AND METHOD</p> <div data-bbox="316 1144 1242 1417"> </div> <p>(57) Abstract</p> <p>A device and method for treatment of a tissue specimen disposed in surrounding tissue has a tissue specimen isolating tool and a tissue specimen damager. The tissue specimen isolating tool isolates the tissue specimen from the surrounding tissue. The tissue specimen damager damages the tissue, with a possible end result being necrosis. The severing tool may have a cutting member that is extendable to an outwardly radially bowed position about device. The tissue specimen is isolated by rotating the cutting member about the tissue specimen. The cutting member may be functionally connected to a cutting member radio frequency generation source. The tissue specimen damager may damage the tissue specimen using ionizing radiation, cutting devices, thermal treatment devices, chemical treatment devices, or sealing an outer boundary of the tissue specimen.</p>		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

TISSUE SPECIMEN ISOLATING AND DAMAGING DEVICE AND METHOD

BACKGROUND OF THE INVENTION

1. Field of the Invention

5 This invention relates to treatment of tissue specimens and, more specifically, to the treatment of the tissue specimens *in vivo*.

2. Description of the Related Art

The prior art discloses devices and methods of isolating a tissue specimen while it remains in surrounding tissue. The prior art also discloses devices and
10 methods of ablating or otherwise damaging a non-isolated tissue specimen *in vivo*. However, the prior art does not disclose, suggest, nor motivate combining the two concepts into one method or device. Additionally, the prior art does not disclose any synergistic effects of combining the two concepts.

It is disclosed in a paper entitled "The Loop Electrode: A New Device For
15 US-guided Interstitial Tissue Ablation Using Radiofrequency Electrosurgery - An Animal Study," T. Lorentzen et al., Min Invas Ther & Allied Technol 1996: 5: 511-516, that a radiofrequency loop is used to perform interstitial tissue ablation. The device was inserted into calf livers and rotated to interstitially cut off lesions. The paper reviews minimally invasive tissue ablation techniques, such as
20 intraoperative cryosurgery and percutaneous methods such as laser, microwaves, radiofrequency electrosurgery, and injection of ethanol or hot saline. The paper also reviews high-focused ultrasound as an example of a non-invasive method. The paper does not disclose, suggest, nor motivate combining the use of a radiofrequency loop with other tissue ablation methods.

25 A procedure is disclosed in a paper entitled "Interstitial Hyperthermia Of Colorectal Liver Metastases With A US-guided Nd-YAG Laser with a Diffuser

Tip: A Pilot Clinical Study,” C. Nolsøe et al., Radiology, 1993; 187:333-337, that involves placing a laser fiber in the center of a tumor and irradiating the tumor to achieve hyperthermia ablation. It is also disclosed to use ultrasound to monitor the temperature of the tumor during the method. The paper discloses a charred
5 border region about the tissue specimen and a coagulated region beyond the charred border. The paper does not disclose any concerns associated with ablating a non-isolated tissue specimen. The paper does not disclose, suggest, nor motivate combining the use of lasers with other tissue ablation methods.

It is disclosed in a paper entitled “Phototherapy of Tumors,” S.G. Brown,
10 World J. Surg. 7, 700-709, 1983, the use of the chemical hematoporphyrin derivative (HpD) in conjunction with a dye laser for tumor therapy. The HpD/dye laser method is not thermal, as is the case with most laser methods, but depends on the production of singlet oxygen by activated HpD. The paper discloses the promise of the HpD/dye laser methods - but with no disclosure, suggestion, or
15 motivation to isolate the tissue specimen prior to treatment. The paper discloses the problems associated with unacceptable damage to surrounding tissue during thermal laser methods.

It is disclosed in a paper entitled “Clinical Thermochemotherapy: A Controlled Trial In Advanced Cancer Patients,” F.K. Storm et al, Cancer 53:863-
20 868, 1984, to combine hyperthermia and chemotherapy for increased drug uptake of cancer cells. The hyperthermia was administered using a magnetrotde magnetic-loop induction device. The paper does disclose the beneficial of preserving the tissue surrounding the tissue specimen, which in the disclosed method is due to coincident vascular occlusion. It does not disclose, motivate, or
25 suggest direct methods of severing vascular connections between a tissue specimen and surrounding tissue, in conjunction with other methods of tissue specimen ablation.

It is disclosed in a paper entitled “Liver Photocoagulation With Diode Laser (805nm) Vs Nd:YAG Laser (1064 nm),” S.L. Jacques et al., SPIE Vol.

1646 Laser-Tissue Interaction III (1992), p. 107-117, that laser treatment results in radially expanding regions of tissue damage. The paper does not disclose, suggest, nor motivate isolating the tissue specimen targeted for necrosis and any result that may have with reducing damage to surrounding tissue.

5 It is disclosed in a paper entitled "MR Imaging Of Laser-Tissue Interactions," F.A. Jolesz, Radiology 1988; 168:249-253, that thermal transfer and damage to surrounding tissue during hyperthermia treatment should be monitored. The paper also discloses that circulatory cooling, among other parameters, affects energy deposition. The paper does not disclose, suggest, nor motivate that
10 isolating the tissue specimen prior to hyperthermia treatment. This information is similarly disclosed in a paper entitled "Temperature Mapping With MR Imaging Of Molecular Diffusion: Application to Hyperthermia," D.L. Bihan, Radiology 1989; 171:853-857.

 Therefore, the prior art discloses damage occurs to tissue surrounding a
15 tissue specimen to be treated. What is needed is a device and method for reducing damage to the surrounding tissue. What is also needed is a device and method with increased efficiency for damaging the tissue specimens.

SUMMARY OF THE INVENTION

 In an aspect of the invention, a tissue specimen that is disposed in
20 surrounding tissue is treated. The treatment comprises an isolation step and a damaging step. During the isolation step, the tissue specimen is isolated from the surrounding tissue by at least partially severing the tissue specimen from the surrounding tissue. Next, the tissue specimen is damaged.

 In an aspect of the invention, the isolating step further comprises the step
25 of moving a tissue specimen isolating tool about the tissue specimen. In a further aspect of the invention, the tissue specimen isolating tool comprises a radio frequency energized wire. The treatment process may include the step of applying a tool charged with radio frequency energy to the tissue specimen.

In aspects of the invention, the damaging step may comprises applying ionizing radiation to the tissue specimen, cutting the tissue specimen, thermally treating the tissue specimen, chemically treating the tissue specimen, or sealing an outer boundary of the tissue specimen.

5 In an aspect of the invention, a device for treatment of a tissue specimen in surrounding tissue comprises an operational portion, a tissue severing tool, and a tissue specimen damager. The tissue specimen isolating tool and the tissue specimen damager are disposed at the operational portion.

In a further aspect of the invention, a radio frequency generation source is
10 functionally connected to the tissue specimen isolating tool.

In an aspect of the invention, the tissue specimen isolating tool of the treatment device comprises a cutting member that is extendable to an outwardly radially bowed position about the operational portion. In a further aspect of the invention, a cutting member radio frequency generation source is functionally
15 connected to the cutting member.

In an aspect of the invention, the tissue specimen damager of the treatment device comprises at least one metal member extending from the operational portion and being functionally connectable to a metal member radio frequency generation source.

20 In aspects of the invention, the tissue specimen damager may comprise an ionizing radiation director, a tissue specimen cutter, a thermal treatment system, or a chemical introduction system.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 shows a side view tissue specimen isolating and damaging device
25 using radio frequency energized wires according to an embodiment of the invention;

Figure 2 shows a sectional view of the device of Figure 1 in a breast after isolation of the tissue specimen and prior damaging the tissue specimen;

Figure 3 shows the same sectional view as does Figure 2 but after damaging the tissue specimen by thermal treatment;

Figure 4 is a nonexclusive chart of treatment methods for damaging the tissue specimen according to embodiments of the invention; and

5 Figures 5-8 are side views of tissue specimen isolating and damaging devices according to various embodiments of the invention.

Figures 9 and 10 show tissue specimen encapsulation devices which may be used in conjunction with the invention.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

10 Referring now to the figures, and specifically to Figure 1, a tissue specimen isolating and damaging device 10 comprises a wand 12 having a proximal end 14 shown to the right and a distal end 16 shown to the left. The device 10 is used to isolate a tissue specimen while the tissue specimen is disposed in surrounding tissue and then damage the tissue specimen (see Figures 2 and 3). The isolation
15 step may encompass isolating the tissue specimen from circulation and/or may encompass generally severing of the tissue specimen from the surrounding tissue. After the damaging step, the tissue specimen may remain in the body, turn into fibrotic tissue, and/or be removed from the body during the process or at a later time.

20 While isolating the tissue specimen may result in necrosis, the device 10 damages the tissue specimen to insure necrosis occurs. The necrosis of the tissue specimen results in reducing or eliminating the transfer of malignant or diseased tissue from the tissue specimen. The necrosis of the tissue specimen also dissuades the patient's body from repairing the tissue specimen. The shown
25 embodiment of the invention utilizes a radio frequency generator 18 to perform the procedure. Other embodiments of the invention may use other methods, examples of which are non-exclusively discussed below.

Located at the distal end 16 of the wand 12 is an operational portion 20 of the device 10. The operational portion 20 is involved with both isolating and damaging the tissue specimen. In the shown embodiment, an outwardly radially bowed wire 22 isolates the tissue specimen. The wire 22 is disposed at the
5 operational portion 20 and rotationally connected to the wand 12. In the shown embodiment of the invention, the wire 22 is initially in a retracted position against the wand 12 (not shown) to reduce trauma to surrounding tissue during placement of the device 10. The wire 22 is extended outward radially after the operational portion 20 is disposed in or proximate to the tissue specimen.

10 The wire 22, which is a tissue specimen isolating tool of the device 10, is powered by the radio frequency generator 18 and rotated to isolate the tissue specimen. As the wire 22 is rotated, a periphery channel (see Figure 2) is formed between the tissue specimen and the surrounding tissue, thus severing the two. Other embodiments of the invention may have the wire 22 be fixedly and not
15 rotatably connected to the wand 12, thus the whole wand is rotated to isolate the tissue specimen and not just the bowed wire 22.

Embodiments of the invention may comprise other tissue specimen isolating tools with cutting members, such as those disclosed in WO 99/44506 published on September 10, 1999. Embodiments of the invention may only
20 partially sever the tissue specimen from the surrounding tissue.

At the distal end 16 is a radio frequency wire 24 that is energized during the step of inserting the wand 12 into the surrounding tissue. Other embodiments may have other means for inserting the wand into the surrounding tissue, such as a non-energized piercing tool or some other form of energized piercing tool. Still
25 other embodiments of the invention may not have a piercing tool at the distal end 16, but rather enter the surrounding tissue through a pre-existing passage.

In the shown embodiment, the tissue specimen is ablated or otherwise damaged after isolation (see Figure 3). The damaging of the tissue sample results in necrosis. The damage may be caused by ionizing radiation that disrupts

cellular functions. The tissue specimen may be damaged through mechanical means, such as cutting or otherwise morcellating the tissue specimen. Tissue specimen damage may be the result of thermal or chemical treatment.

Continuing to refer to Figure 1, radio frequency wires 28 that extend from
5 the operational portion 20 of the device 10 are used to damage the tissue specimen. The wires 28 are initially in a retracted position in wand 12 or disposed on the wand 12. Either before, during, or after the isolation of the tissue specimen, the wires 28 are extended as shown and enter the tissue specimen. In a preferred embodiment of the invention, the wires 28 are disposed in the wand 12
10 and are extended prior to isolation of the tissue specimen. The extended wires 28 anchor the device 10 in the tissue specimen, resulting in a more precise isolation of the specimen. Other embodiments of the invention may have other methods or mechanisms for anchoring the device 10 in the tissue specimen.

The radio frequency wires 28, which comprise the tissue specimen
15 damager of device 10, are shown extending toward the distal end 16 of the wand 12. Other embodiments of the invention may have wires 28 extending in any suitable direction. The wires 28 are shown extending almost to the radially bowed wire 22, resulting in the wires 28 being distributed throughout the tissue specimen. Other embodiments of the invention may have the wires 28 extending
20 into a portion of the tissue specimen.

When energized, the radio frequency wires 28 damage the tissue specimen by causing the water molecules in the tissue specimen to vibrate and rapidly vaporize. The rapid vaporization results in the destruction of cells in the tissue specimen, thus damaging the specimen. The rapid vaporization is a form of
25 thermal treatment. The radio frequency wires may be mono- or bi-polar.

After treatment, the wires 28 may be retracted into the wand 12. Other embodiments of the invention may not have the wires 28 being retracted, but rather the wires 28 remain extended and slide out of the tissue specimen during

removal of the wand 12 from the surrounding tissue. The distally leaning wires 28 facilitate their sliding out of the tissue specimen during wand removal.

The severing and isolation of the tissue specimen results in a more controlled and simpler process to damage the specimen. In the case of thermal treatment, a non-isolated tissue specimen is cooled or heated by blood circulating through the specimen. The thermal treatment of an isolated tissue specimen is not competing with the cooling or heating effects of blood circulation. Without competing with the effects of blood circulation through the specimen, the thermal treatment is shorter and more restricted to the immediate tissue specimen.

10 Further, the isolation reduces thermal damage to the surrounding tissue.

Functionally connected to the proximal end 14 of the wand 12 is a control system 30. In the shown embodiment, the control system 30 manipulates the cutting wire 22 and the radio frequency wires 28. In some embodiments of the invention, the control system 30 may control the insertion and removal of the wand 12 from the tissue specimen and the surrounding tissue. The control system 30 is functionally connected to the radio frequency generator 18 that supplies energy to the wires 22 and 28. In the embodiments of the invention in which the radially bowed wire 22 is in a fixed position on the wand 12, the control system 30 rotates the wand 12 to isolate the tissue specimen. In other embodiments of the invention, the components of the device are manipulated by hand.

Referring now to Figure 2, the device 10 is shown disposed in a breast 50 with the operational portion 20 being disposed in a tissue specimen 52. In this embodiment, the breast 50 may be considered the surrounding tissue. The tissue specimen 52 contains a tumor 54, which is shown cross-hatched. The cutting wire 22 is shown in the outwardly radially bowed position. The cutting wire 22 has already been rotated, thereby forming a periphery channel 56 and isolating the tissue specimen 52. Note the radio frequency wires 28 are not shown extended in Figure 2. In a preferred embodiment of the invention, the wires 28 are extended into the tissue specimen 52 prior to isolation.

Referring now to Figure 3, the tissue specimen 52 of Figure 2 has been damaged, resulting in damaged tissue specimen 60 through thermal treatment by the device 10. The radio frequency wires 28 of the device 10 are shown extended 10 into the tissue specimen 60. The wires 28 had been energized, resulting in the
5 vaporization of the water molecules, disruption of the cells of the tissue specimen, heating the specimen, and the ultimate damaging of it. The amount and time of the treatment may be predetermined or the device may comprise a feed back system (not shown) that indicates when the treatment has been completed. In a further step, the device 10 is removed from the breast 50, either with or without
10 retracting the radio frequency wires 28 into the device 10.

Referring now to Figure 4, Chart 100 is a non-exclusive list of possible methods for damaging the *in vivo* tissue specimen besides thermal treatment through radio frequency devices. Listed as forms of thermal treatments 102 are
15 laser, hot fluids, cold fluids, radio frequency energy and other electrosurgery techniques, microwave, focussed ultrasound, mechanical ultrasound, shock waves, resistive heating, cryosurgery using liquid or gas, cauterizing, and the application of a heated object. An example of a heated object is disclosed in U.S. Patent No. 4773413 to Hussein et al. entitled "Localized Heat Applying Medical Device," which is incorporated herein by referenced in its entirety. Other embodiments of
20 the invention may use any suitable thermal treatment system to damage the tissue specimen.

The mechanical treatment list 104 includes morcellators and other cutting devices. The ionizing radiation treatment list 106 includes treatment with x-rays, including x-ray needles, gamma rays, and Brachytherapy seeds, which are forms
25 of ionizing radiation directors. The chemical treatment list 108 includes treatment with ethanol, sotradechol, an acid, a base, various chemical compounds, various chemical mixtures, a catalyst, a sealing agent that seals the outside of the tissue specimen, and a photoreactive chemical that is used in conjunction with a light or

laser system. Other embodiments of the invention may use any suitable chemical treatment system to damage the tissue specimen.

Referring now to Figure 5, a tissue specimen isolating and damaging device 200 has a laser device 202 at an operational portion 204. The laser device 202 damages a tissue specimen through thermal treatment. The shown embodiment of the invention has two outwardly radially bowed cutting wires 206. Embodiments of the invention may have one or more cutting wires 206 regardless of the treatment to damage the tissue specimen. Note that a cutting tip 210 is located at a distal end 212 of the device 200.

Referring now to Figure 6, a tissue specimen isolating and damaging device 220 has a morcellator 222 at an operational portion 224. The morcellator 222 is used to morcellate a tissue specimen. The tissue specimen may be morcellated after encapsulation of the tissue specimen. Encapsulation of the tissue specimen may be accomplished by use of a tissue specimen encapsulation device as shown in Figure 9. The figure depicts a tissue specimen encapsulation device 310 which is comprised of a wand assembly 312, a sheath 314, and a guide assembly 316. The wand assembly 312 defines an axis 318, and axial direction 320, and a plurality of radial directions 322. The wand assembly 312 also has a proximal end 324, shown to the left in Figure 9, and a distal end 326, shown to the right in Figure 9. A midsection 328 extends between the ends 324 and 326. The proximal end 324 is the end that is held by a user of the device 310. The proximal end 324 may be functionally connected to an actuator system, such as a control box or the equivalent, that manipulates the device 310 per the directions of the user (not shown). The distal end 326 is inserted into a target body (not shown) and proximate to a tissue specimen to be encapsulated by the device. The wand assembly 312 may be rigid or flexible, and may be articulatable so that it may be steered. The wand assembly 312 comprises a shaft core 329, shaft 330, a sheath sleeve 332 and an outer sleeve 334. The shaft core 329, shaft 330 and sleeves 332 and 334 are co-axially aligned and nested such that the shaft core 329 is inside the

shaft 330 that is inside the sheath sleeve 332 that is inside the outer sleeve 334. The shaft core 329 and the shaft 330 extend proximally and distally beyond the sleeves 332 and 334 with the shaft core extending proximally beyond the shaft. The sheath sleeve 332 extends proximally beyond the outer sleeve 334 but the
5 outer sleeve 334 extends distally beyond the sheath sleeve 332. In the device as shown, the distal end 326 of the device has a tip 338 with a radio frequency ("RF") powered member 340 extending diametrically across the tip. The RF powered member 340 may be energized such that the device moves through tissue via ablation or electrosurgical incision, thus enabling the device to be inserted into
10 the target body containing a tissue specimen to be encapsulated. The device also may enter the biological target via other means, such as lasers or other focussed light techniques, high pressure water, cutting with a sharp implement, cryogenic techniques, etc. In addition, the device may not have a component analogous to the RF powered member 340 but the distal end 326 may be inserted into the target
15 body through a pre-existing passage (not shown). The device also has a sheath deployment rod deployment end 342 extending from the proximal end 324 of the wand assembly 312. The sheath deployment member deployment end 342 is pulled proximally in the axial direction 320 to deploy the sheath 314 about a tissue specimen. In Figure 10, the sheath deployment members 448 are shown
20 deployed about the tissue specimen 491. At the axial center of the wand 412 is the sheath deployment member deployment rod 456. The sheath deployment member deployment rod 456 extends distally through the sheath deployment member cap 454 and terminates at the stop 488. The stop 488 is located distally and adjacent to the cap top 476. The sheath deployment member cap 454 is
25 located at the distal end 426 of the wand assembly 412 with the axial extensions 478 extending proximally. The axial extensions 478 are disposed against the interior surface of the shaft core 429. The sheath deployment member deployment ends 474 are looped around the sheath deployment member ring 482, which is located proximal to the cap top 476. The sheath deployment members

448 extend from the sheath deployment member ring 482 and radially out of the distal end 426 of the shaft 430. As shown in Figure 10, the sheath deployment member deployment rod 456 is centrally located within the shaft core 429. The push rods 452 are disposed in grooves 458 in the outer surface of the shaft core 429. The shaft 430 surrounds the shaft core 429. The tissue specimen 492 is disposed about the shaft 430 toward the shaft's distal end 426. The outer sleeve 434 is shown surrounding the shaft 430 and is located proximally from the tissue specimen 492. The sheath 414 is disposed between the shaft 430 and the outer sleeve 434 with the second portion 446 distally extending from under the outer sleeve. The sheath deployment members 448 are deployed about the tissue specimen 492 but have not been released from the wand assembly 412. The end balls 470 of the sheath deployment members 448 are disposed in the ball-holders 466. The push rods 452 have been pushed to a position proximal of ball openings 402. The ball openings 402 are located at the proximal end of each sheath deployment member slot 472 and extend through the shaft 430. The ball openings 402 generally correspond with the proximal end of the tissue specimen 492. The sheath deployment members 448 extend from the end balls 470, through the ball openings 402, through ligatures 449 extending from the sheath second portion 446, and into the periphery margin 498 about the tissue specimen 492.

The tissue specimen may be encapsulated with non-bio degradable or biodegradable material. Note that there is not a piercing tool on this embodiment of the invention. Other morcellating devices may have a piercing tool. Also note that the cutting wire is in a retracted position and not visible.

In an embodiment of the invention, the tissue specimen is damaged by encapsulation. The damage is the result of the tissue specimen being physically isolated from the surrounding tissue. In an embodiment of the invention, a sheath may at least partially surround the tissue specimen (not shown). In another embodiment of the invention (not shown), the tissue specimen may be physically isolated by encapsulation accomplished with a chemical that flows into the

periphery channel about the tissue specimen and seals specimen's outside surface. Suitable techniques known in the art for ensuring a continuous distribution of the sealing chemical may be employed, such as pressurizing the periphery channel.

Now referring to Figure 7, a tissue specimen isolating and damaging device
5 240 has outlets 242 at the operational portion 244. The outlets 242 permit the flow of a chemical into the tissue specimen, thus transforming the tissue specimen through a chemical reaction or other chemical treatment. The isolation of the tissue specimen reduces the amount of chemicals transferring to the surrounding tissue.

10 In other embodiments of the invention, hollow needles may extend from the operational portion 244 such that the chemical may be injected into the tissue specimen through the needles. Other embodiments of the invention may include slicing tools that make slits in the surface of the tissue specimen that is in contact with the wand 246. The slits facilitate infusion of the chemical. The slits may
15 also be made by the cutting wire 248. The cutting wire 248 is rotated and partially extended into the tissue specimen at periodic intervals either before or after the tissue specimen has been isolated.

Referring now to Figure 8, a tissue specimen isolating and damaging device 260 cryogenically treats the tissue specimen 262 disposed at the
20 operational portion 264 of the wand 266. A cryogenic fluid is flowed to the operational portion 264 through a feed line 268 and is returned to the control system (not shown) via a return line 270, both of which is disposed in the wand 266. The tissue specimen 262 is frozen and damaged through thermal treatment with the cryogenic fluid.

25 Embodiments of the invention have suitable control systems incorporated into the tissue specimen isolating and damaging device. Further, the embodiments of the invention are suitably configured for different treatment methods and different tissue specimen shapes and sizes.

Although presently preferred embodiments of the present invention have been described in detail hereinabove, it should be clearly understood that many variations and/or modifications of the basic inventive concepts herein taught, which may appear to those skilled in the pertinent art, will still fall within the
5 spirit and scope of the present invention, as defined in the appended claims.

CLAIMS

1. A device for treatment of a tissue specimen in surrounding tissue comprising:
 - a. an operational portion;
 - b. a tissue specimen isolating tool disposed at the operational portion; and
 - c. a tissue specimen damager disposed at the operational portion.
2. The treatment device of claim 1, further comprising a radio frequency generation source that is functionally connected to the tissue specimen isolating tool.
3. The treatment device of claim 1, wherein the tissue specimen isolating tool comprises a cutting member that is extendable to an outwardly radially bowed position about the operational portion.
4. The treatment device of claim 3, further comprising a cutting member radio frequency generation source that is functionally connected to the cutting member.
5. The treatment device of claim 4, wherein the tissue specimen damager comprises at least one metal member extending from the operational portion and being functionally connectable to a metal member radio frequency generation source.
6. The treatment device of claim 1, wherein the tissue specimen damager comprises an ionizing radiation director.

7. The treatment device of claim 1, wherein the tissue specimen damager comprises a tissue specimen cutter.
8. The treatment device of claim 1, wherein the tissue specimen damager comprises a thermal treatment system.
9. The treatment device of claim 1, wherein the tissue specimen damager comprises a chemical introduction system.

1/6




FIG. 1




FIG. 2

2/6




FIG. 3

3/6

100

METHODS OF DAMAGING *IN VIVO* TISSUE SPECIMENS

THERMAL TREATMENT	MECHANICAL TREATMENT	IONIZING RADIATION TREATMENT	CHEMICAL TREATMENT
LASER HOT FLUIDS COLD FLUIDS RADIO FREQUENCY ENERGY MICROWAVE FOCUSSED ULTRASOUND MECHANICAL ULTRASOUND SHOCK WAVES RESISTIVE HEATING CRYOSURGERY CAUTERIZERS HEATED OBJECTS	MORCELLATORS OTHER CUTTING TECHNIQUES	X-RAYS (NEEDLE) GAMMA RAYS BRACHYTHERAPY SEEDS	ETHANOL SOTRADECHOL ACIDS BASES CHEMICAL COMPOUNDS CHEMICAL MIXTURES PHOTOREACTIVE CHEMICALS SEALERS

FIG. 4

4/6




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10

INTERNATIONAL SEARCH REPORT

Int. Application No

PCT/US 00/02155

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 A61B18/14

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A61B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 858 774 A (ETHICON ENDO SURGERY INC) 19 August 1998 (1998-08-19) column 5, line 29-47 column 10, line 31-53	1,2,4,5, 7
Y	ref sign 24 figures 1,2,10	3
Y	GB 2 311 468 A (VALLEYLAB INC) 1 October 1997 (1997-10-01) ref sign 18 abstract; figures 1,3	3
A	US 5 827 268 A (LAUFER MICHAEL D) 27 October 1998 (1998-10-27) ref sign 42 48 60 figures 15-18	1
-/-		

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

21 March 2000

Date of mailing of the international search report

06/04/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 681 epo nl,
Fax (+31-70) 340-3018

Authorized officer

Papone, F

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 00/02155

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 97 29702 A (RITA MEDICAL) 21 August 1997 (1997-08-21) abstract; figures 1,2	1
X	US 5 743 906 A (POPPE RICHARD KEITH ET AL) 28 April 1998 (1998-04-28) abstract; figure 7	1,2
X	US 5 295 990 A (LEVIN JOHN M) 22 March 1994 (1994-03-22) abstract; figure 1	1,2
P,A	WO 99 44506 A (SENORX) 10 September 1999 (1999-09-10)	

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 00/02155

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 0858774	A	19-08-1998	US 5913857 A AU 5036198 A CA 2227348 A JP 10201764 A	22-06-1999 23-07-1998 21-07-1998 04-08-1998
GB 2311468	A	01-10-1997	CA 2200029 A DE 19706751 A FR 2746628 A	27-09-1997 02-10-1997 03-10-1997
US 5827268	A	27-10-1998	AU 4897797 A WO 9818393 A US 6004316 A	22-05-1998 07-05-1998 21-12-1999
WO 9729702	A	21-08-1997	US 5728143 A AU 2254397 A CN 1211171 A EP 0883379 A US 5800484 A	17-03-1998 02-09-1997 17-03-1999 16-12-1998 01-09-1998
US 5743906	A	28-04-1998	US 5603711 A	18-02-1997
US 5295990	A	22-03-1994	NONE	
WO 9944506	A	10-09-1999	AU 2976599 A	20-09-1999

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.